



BETWEEN INTERSECTIONS EXCEED 360', AN INTERMEDIATE STREETLIGHT, OR STREETLIGHTS, SHALL BE INSTALLED. SPACING OF STREETLIGHTS BETWEEN INTERSECTIONS WHERE REQUIRED TWO STREETLIGHTS SHALL BE INSTALLED AT EACH INTERSECTION. SHOULD THE DISTANCE SHALL BE 150' MINIMUM TO 220' MAXIMUM.

STREETLICHTS SHALL BE INSTALLED AT LOCATIONS AS DETERMINED BY THE CITY ENGINEER

UPON REVIEW OF SUBMITTED IMPROVEMENT PLANS.

2

ω;

STREETLIGHTS SHALL BE INSTALLED ON BOTH SIDES OF THE STREET IN A STAGGERED

4.

IF AN INTERSECTION IS SIGNALIZED, A STREETLIGHT SHALL BE INSTALLED ON EACH CORNER AS A PART OF THE TRAFFIC SIGNAL SYSTEM. 5

ALL STREETLIGHTS INSTALLED OR REPLACED IN THE CENTRAL BUSINESS DISTRICT ARE SUBJECT TO APPROVAL BY THE CITY ENGINEER. છં

| MEDIAN CURB | DKA |
|------------------------------|-----|
| Michael W. Miller | |
| Approved By: | |
| Date: 08/07/17 City Engineer | |

DRAWING NO.:

7320

1 OF 1