

CONCRETE REMOVAL

DESCRIPTION

- 1501.1 Concrete shall be removed at the locations shown on the plans or described in the Special Provisions or where directed by the engineer. Removal shall be to the lines and elevations shown, specified or determined by the engineer.

Concrete shall be defined as Portland Cement Concrete curbs, gutters, sidewalks, gutter depressions, driveways, approaches, footings, and all other Portland Cement Concrete or masonry construction.

- 1501.2 Removal Methods: Existing concrete shall be removed to its full depth unless otherwise specified. Concrete shall be cut to a true line where new concrete is to join existing concrete.

Concrete removal operations shall be performed without damage to any portion that is to remain in place. All damage to the existing concrete, which is to remain in place, shall be repaired to a condition equal to that existing prior to the beginning of removal operations. The cost of repairing existing concrete damaged by the Contractor's operations shall be at Contractor's expense.

- 1501.3 Disposal: The Contractor shall make arrangements for disposing of the broken concrete.

MEASUREMENT AND PAYMENT

- 1502.1 Measurement: The work performed under "**Concrete Removal**" and paid for by contract items will be measured by the cubic yard, or by the square yard of surface area or by other methods specified on the plans or in the Special Provisions.

- 1502.2 Payment: Items of work, measured as specified above, will be paid for at the price per cubic yard or lump sum price for removing concrete; or as otherwise provided by the plans or Special Provisions.

The above prices and payments shall include full compensation for furnishing all labor, materials, tools, equipment and incidentals and for doing all the work involved in removing and disposing of the concrete as specified in these specifications and the Special Provisions and as directed by the Engineer.